



TAG Carburetor Quick Reference Specifications

ENGINE NAME	CARBURETOR	VENTURI	BORE
BM Jaguar	Tillotson 334A. AB or AA	0.905"	1.010"
Cheeta SQ125	Tillotson 334A. AB or AA	0.905"	1.010"
Easykart	Tillotson 384B		
Motori Seven TAG L4	Dell'Orto VHSH30CS	1.185"	1.190"
Parilla Leopard '03	Tillotson 334A. AB or AA	0.905"	1.010"
PRD Fire Ball 2005	Tillotson 360A	0.950"	1.065"
*PRD Fire Ball 2008	Tillotson 360A	0.950"	1.065"
Rotax Max FR 125	Dell'Orto VHSB 34		
Sonik TX125	Tryton VAMECM1	0.943"	1.075"
Sonik VX125 (118)	Tryton VAMECM1	0.943"	1.075"
Vortex ROK TT	Tillotson 360A	0.950"	1.065"

Carburetor venturi diameter checked at narrowest point of venturi.

Easykart has a fixed high-speed jet, no polishing of carburetor allowed. Butterfly stop in bore must be in place.

Note: No specs are currently available for the Tillotson 384B on the Easykart. The specs for the Dell'Orto VHSB 34 on the Rotax Max FR 125 are per RMC rules